

KOMPATTO Standard

Versions		Standard M10	Standard M12	Standard M17
Max production capacity		10 m ³ /hr	12 m ³ /hr	17 m ³ /hr
Designed for		producing up to 10 m ³ /hr Screeds/ roofs	producing up to 12 m ³ /hr Screeds/ roofs	producing up to 17 m ³ /hr Screeds/ roofs
Other applications		Blocks / Panels Geotechnical	Blocks / Panels Geotechnical	Blocks / Panels Geotechnical
Dimensions		195x145x108 cm		
Weight		780 kg	800 kg	800 kg
Power		12 Kw	14 Kw	17 Kw
Foam production capacity		250 lt/min	250 lt/min	500 lt/min
Max pumping capacity		350 lt/min	500 lt/min	500 lt/min
Maximum Dry Density		600 kg/m ³	600 kg/m ³	600 kg/m ³
Max pumping distance	Vertical	45 mt	45 mt	45 mt
	Horizontal	90 mt	90 mt	90 mt
Optional fittings	Anti dust doors	Applicable		
	Ews	Applicable		
	Digital Timer	Applicable		
	Foam Generator 500 lt/min	Applicable (+ 3 m ³ /hr) Total: 13 m ³ /hr	Applicable (+ 5 m ³ /hr) Total: 17 m ³ /hr	Included
	MiV	Applicable		
Optional Accessories		Applicable		
Optional Equipment		Applicable		